Norsat International Inc.

Innovative Communication Solutions

TRF-C

Transmit Reject Filter for LNB Redundancy Switch

Configuration: for C-Band



KEY SPECIFICATIONS

Center Frequency	3.8 GHz
Frequency Range	3.4 – 4.2 GHz
Out-Of-Band Rejection	≥ 80dB @0.58 - 0.71 GHz
Product Revision	A

RF SPECIFICATIONS

Insertion Loss	0.3 dB max, 0.2 dB typ.
VSWR	1.25 : 1 max

ELECTRICAL SPECIFICATIONS

Impedance	50 Ω

INTERFACE SPECIFICATIONS

Connector	WR 229 (Waveguide), CPR 229G (Flange)

ENVIRONMENTAL SPECIFICATIONS

Barometric Pressure	55 KPa - 106 KPa
IP Rating	IP 65
Relative Humidity	5% - 95%
Temperature Operational	-40°C to +60°C
Temperature Storage	-40°C to +85°C

PHYSICAL SPECIFICATIONS

Product Height	70 mm
Product Length	100 mm
Product Weight	0.5 kg
Product Width	99 mm


sales@norsat.com
www.norsat.com

© Copyright Norsat International Inc. All Rights Reserved. Specifications are subject to change without notice. Final product may not be as illustrated. The information contained herein does not constitute part of any order or contract.

SHIPPING INFORMATION

HS Code	-
Country of Origin	Made in Thailand
Ex Works	Richmond, BC, Canada
ECCN Number	EAR99
Warranty	3 years
Unit Package Dimensions	217 mm x 122 mm x 100 mm
Unit Package Weight	0.3 kg
Total Aluminium Content	-
Aluminum Country of Smelt and Cast	-
Total Aluminium Value	-

MECHANICAL DIAGRAMS



© Copyright Norsat International Inc. All Rights Reserved. Specifications are subject to change without notice. Final product may not be as illustrated. The information contained herein does not constitute part of any order or contract.