



10W Ext. Ku-Band Block Up Converter

KEY FEATURES


- ◆ Output frequency 13.75-14.50 GHz
- ◆ Based on GaN technology which enables high efficiency, low energy consumption and high reliability
- ◆ Double - L.O. (electronically and manually switchable 12.80 and 13.05 GHz)
- ◆ Extreme P-Out GaN linearity
- ◆ Auto-ranging power 15-60 VDC
- ◆ Incomparable low power consumption (58W max) - can be powered by some iDirect or similar modems
- ◆ Digital temperature compensation
- ◆ L.O. lock and amplifier LEDs
- ◆ Field-exchangeable (F/N) IF connector
- ◆ M&C - combined RS-232/485, FSK, Ethernet (optional)
- ◆ Internal 10MHz high stability reference (optional)
- ◆ RoHS Compliant

ABE10KFX / ABE10KFXF



This smallest and lightest 10W L-To Ku-Band Block Up Converter is based on GaN technology. Incomparable low power consumption, double L.O., Field-Exchangeable connector and auto-ranging (24 or 48 VDC) powering features make unit universal for any Ku-Band application. M&C (FSK) capability enables troubleshooting, monitoring and controlling the BUC. User can choose internal 10MHz high stability reference if the corresponding modulator does not provide it.

Mechanical Drawing





10W Ext. Ku-Band Block Up Converter

TECHNICAL SPECIFICATIONS		
RF frequency		13.75 to 14.50 GHz
Local oscillator- electronically and manually switchable		13.05 GHz and 12.80 GHz
IF frequency		950 to 1,700 MHz
Output power		10W (+40 dBm min) 5W P-Linear (+37 dBm min)
IF connector		N-type or F-type (field-exchangeable)
Power supply - auto-ranging		+15~+60 VDC via IF cable, 58 W max
Output interface		WR-75 G
Gain		60 dB min., 66 dB max
IMD3		-28 dBc max
L.O. leakage		-45 dBm max
Spurious		-50 dBc max
Spectral regrowth (QPSK at 1.5x and OQPSK at 1.0x symbol rate offset with 2dB back-off from rated output power)		-30 dBc
Gain variation	over 40 MHz over 500 MHz	+/-1.5 dB +/-1.4 dB
Over operating temperature		+/-1.3 dB @ fixed frequency
Requirement for external reference	frequency input power	via IF cable 10 MHz (sine-wave) -5 to +5 dBm @ input port
Phase noise (Exceeds Intelsat's standard IESS308/309)		-53 dBc/Hz max. @ 10 Hz -63 dBc/Hz max. @ 100 Hz -73 dBc/Hz max. @ 1 KHz -83 dBc/Hz max. @ 10 KHz -93 dBc/Hz max. @ 100 KHz -113 dBc/Hz max @ 1 MHz
Noise power density	Transmit Receive	-60 dBm/Hz (max) -151 dBm/Hz (max)
Noise figure		20 dB max
Input V.S.W.R.		1.5 : 1 max
Output V.S.W.R.		1.5 : 1 max.
Mute		Shut off the BUC in case of L.O. unlocked
M&C		RS-232 and RS-485, Ethernet
FSK		Multiplexed on TX IFL, compatible with Comtech and Paradigm
Status LED	RED GREEN YELLOW YELLOW blinking	Summary alarm All OK All OK standard L.O. 13.05 GHz All OK extended L.O. 12.80 GHz
Temperature range (ambient)	operating storage	-40 deg C to +55 deg C -55 deg C to +85 deg C
Vibration and shock		Complies with MIL-STD-810E
Dimensions & housing		120 (L) x 120 (W) x 77 (H) mm 4.72" (L) x 4.72" (W) x 3.28" (H)
Weight		1.4 kg (3.0 lbs) max