



ESER620KU2B

ANCHOR 6.2m Ku-Band Earth Station Antenna

of Ports: 2-ports

We recommend purchasing the corresponding Antenna Control System along with the **motorized** Earth Station, unless you plan to develop the control system yourself. Please note that the Antenna Control System is sold separately at an additional cost.

For Manual Structure Antennas, a control system is not required.

For the 6.2m Ku-Band Earth Station Antenna, **both** the single-speed and dual-speed control systems are compatible. We recommend the dual-speed control system for its flexibility in offering both high and low drive speeds. However, you are also welcome to choose the more cost-efficient single-speed option, which provides a constant drive speed.



KEY SPECIFICATIONS

Band	Ku-Band
------	---------

ANTENNA SPECIFICATIONS

Antenna Aperture	6.2m
Antenna Drive Mode	3-axis motorized structure
Antenna Type	Ring Focus
Number Of Ports	2-ports
Polarization	Linear
Rx Axial Ratio 2 Ports	1.2 dB
Rx Cross Polarization Isolation	≥30 dB
Sidelobe	≤-14dB; $29 - 25 \log\theta (1^\circ \leq \theta < 20^\circ)$
Tx Axial Ratio 2 Ports	1.2 dB
Tx Cross Polarization Isolation	≥30 dB

RF SPECIFICATIONS

Noise Temperature Elevation 10°	50 K
Noise Temperature Elevation 30°	39 K
Noise Temperature Elevation 50°	36 K
Port Isolation Rx-tx	85 dB
Rx Feed Insertion Loss	≤0.35 dB
Rx Frequency	10.70 - 12.75 GHz
Rx Gain	55.85 @ 11.85GHz



Innovative Communication Solutions

Rx VSWR	1.3 : 1
Tx Feed Insertion Loss	≤0.35 dB
Tx Frequency	13.75 - 14.50 GHz
Tx Gain	57.37 @ 14.125GHz
Tx VSWR	1.3 : 1

ELECTRICAL SPECIFICATIONS

Power Capacity	2 KW
----------------	------

INTERFACE SPECIFICATIONS

Rx Interface	WR-75
Tx Interface	WR-75

ENVIRONMENTAL SPECIFICATIONS

Humidity	1.0
Ice Load	Icing 13mm: normal work; Icing 25mm: no damage
Seismic Capacity Horizontal	0.3 G
Seismic Capacity Vertical	0.1 G
Temperature Operational	-30 - 50°C
Windspeed Operational	72 km/h
Windspeed Survival	216 km/h

PHYSICAL SPECIFICATIONS

Loading Capacity	1 set for 40ft container
Motion Range AZ	±70°(Truss type), 5° - 355° continuous (turntable type)
Motion Range EL	5° - 90°
Motion Range POL	±90°
Product Package Volume	5 packages, dimension: 22 CBM
RMS	≤0.5 mm
Structure	LMC/ FMC

LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8529109090	Made in China	China		3590 kg

HOW TO ORDER



EARTH STATION

ESES180KU2A

E SERIES

ANTENNA
STRUCTURE

BLANK: Manual Structure
A: 2-axis Motorized Structure
B: 3-axis Motorized Structure

OF PORTS

2: 2-ports
4: 4-ports

BAND

KA: Ka-Band
KU: Ku-Band

ANTENNA
APERTURE

180: 1.8m
240: 2.4m
370: 3.7m
450: 4.5m
620: 6.2m
730: 7.3m
900: 9.0m
1300: 13.0m

ANTENNA TYPE

C: Cassegrain
S: Single Offset
R: Ring Focus

MECHANICAL DIAGRAMS

