

PerfectLink™

Category 6A Cable

PCAUVXM



General Description

CAT6A (500MHz), 4-Pair, U/UTP-Unshielded, Riser-CMR, CMX Outdoor, Premises Horizontal Cable, Pair separator, Ripcord

Usage (Overall):

Premises Horizontal Cable, Outdoor, Riser, Gigabit Ethernet, 100BaseTX, 100BaseVG, ANYLAN, 155ATM, 622ATM

Performance Specifications

Specification	Value
Conductors (4 Pairs)	AWG: 23
Conductor Material	BC - Bare Copper
Insulation Material	PO-Polyolefin
Jacket	UV Resistant PVC (720 hr)
Nominal Diameter	0.275in (7.0mm)
Suitability	Indoor, Outdoor, Sunlight Resistant, Oil Resistant
Storage Temperature Range	-40°F to 167°F (-40°C To 75°C)
Installation Temperature Range	-4°F to 167°F (-20°C To 75°C)
Operating Temperature Range	-40°F to 167°F (-40°C To 75°C)
UL Temperature Range	75C (UL AWM Style 444)
Bulk Cable Weight	30 lbs/1000 ft
Max Recommended Pulling Tension	40 lbs
Min. Bend Radius/Minor Axis	0.750 in (19.05 mm)
Min. Bend/Installation	2.50 in (63.5 mm)

Electrical Properties

Specification	Value
Capacitance (pF/ft)	17
Delay (ns/100 m)	537 @ 100 MHz
DCR Unbalance @ 20°C	3%
Nominal Velocity of Propagation VP (%)	64
DCR @ 20°C (Ohm/100m)	7.3
NEC/(UL) Specification	CMG, CMR, CMX-Outdoor Telecommunications
Standards	Category 6A - TIA 568.C.2, UL444



Ordering Information

Example	PCAUVXM -	WHT	R	1000
Character	PCAUVXM -	1	2	3

1. Jacket Color	2. Packaging	3. Length
WHT = White	R = Reel	1000 = 1,000 ft
BLK = Black		
GRY = Grey		

Unless otherwise specified, dimensions, material, electrical, and mechanical specifications shall comply with ANSI/TIA/EIA-568-C.2
*Cable image for reference only. Other colors, packaging, lengths available upon request



These products may be protected by one or more patents. For further information, please visit: www.ppc-online.com/patents

6176 E. Molloy Rd. East Syracuse, NY 13057
bbs.cs@belden.com
1-800-800-6652 • +1 315-431-7200



www.ppc-online.com



r3_11012023